

1N5817HT THRU 1N5819HT


Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 20 to 40 V

Forward Current - 1 A

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Absolute Maximum Ratings and Characteristics


Ratings at 25°C ambient temperature unless otherwise specified, single phase, half wave, resistive or inductive load. For capacitive load, derate by 20%

Parameter	Symbols	1N5817HT	1N5818HT	1N5819HT	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	V
Maximum RMS Voltage	V_{RMS}	14	21	28	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1			A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC methode)	I_{FSM}	25			A
Maximum Instantaneous Forward Voltage at $I_F = 1$ A at $I_F = 3$ A	V_F	0.45 0.75	0.55 0.875	0.6 0.9	V
Maximum Instantaneous Reverse Current at Rated DC Blocking Voltage ¹⁾ $T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$	I_R	0.5 10			mA
Typical Junction Capacitance ²⁾	C_J	110			pF
Typical Thermal Resistance, Junction to Ambient ³⁾	$R_{\theta JA}$	75			°C/W
Operating Junction Temperature Range	T_j	- 55 to + 125			°C
Storage Temperature Range	T_{stg}	- 55 to + 150			°C

¹⁾ Pulse test: 300 μs pulse width, 1% duty cycle

²⁾ Measured at 1 MHz and reverse voltage of 4 V

³⁾ Thermal resistance junction to ambient 0.24" X 0.24" (6 X 6 mm) copper pads to each terminals



1N5817HT THRU 1N5819HT

Fig 1. Forward Current Derating Curve




Fig 2. Junction Capacitance Reverse Voltage





Fig 3. Forward Characteristics




1N5817HT THRU 1N5819HT

PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SOD-323HE



UNIT	A	B	C	D	E	F1	F2	G1	G2	H _E
mm	0.7	0.02	0.2	2	1.35	0.95	0.7	1.5	0.6	2.6
	0.5	0	0.1	1.8	1.15	0.75	0.5	1.3	0.4	2.4

Recommended Soldering Footprint



Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOD-323HE	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

Marking information

" III " = Cathode line

" ** " = Part No.

Font type: Arial

