



BAT721 / A / C / S

Silicon Epitaxial Planar Schottky Barrier Diode

For small current rectification and switching applications




BAT721 Marking Code: **L7**
BAT721A Marking Code: **L8**
BAT721C Marking Code: **L9**
BAT721S Marking Code: **L0**
TO-236 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Reverse Voltage	V_R	40	V
Average Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current (8.3 ms)	I_{FSM}	1	A
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 65 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Typ.	Max.	Unit
Forward Voltage at $I_F = 10\text{ mA}$ at $I_F = 100\text{ mA}$ at $I_F = 200\text{ mA}$	V_F	- - -	300 420 550	mV
Reverse Current at $V_R = 30\text{ V}$ at $V_R = 30\text{ V}, T_J = 100^\circ\text{C}$	I_R	- -	15 3	μA mA
Diode Capacitance at $V_R = 0\text{ V}, f = 1\text{ MHz}$	C_d	23	50	pF



Electrical Characteristics Curves

Fig 1. Diode Capacitance vs Reverse Voltage




Fig 2. Reverse Current vs Reverse Voltage







Fig 3. Forward Current vs Forward Voltage




PACKAGE OUTLINE

Plastic surface mounted package (Dimensions in mm)

TO-236



Recommended Soldering Footprint



Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
TO-236	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

Marking information

" ** " = Part No.
"YM" = Date Code Marking
"Y" = Year
"M" = Month
Font type: Arial

