

S1ABD THRU S1MBD

Surface Mount General Rectifier

Reverse Voltage – 50 to 1000 V


Forward Current – 1 A

Features

- The Plastic package carries Underwriters Laboratories Flammability Classification 94V-0
- For surface mounted applications
- Low reverse leakage
- Built-in strain relief, ideal for automated placement
- High forward surge current capability

Mechanical Data

- **Case:** JEDEC DO-214AA, molded plastic body
- **Terminals:** Solder plated, solderable per MIL-STD-750, Method 2026
- **Polarity:** Color band denotes cathode end
- **Mounting Position:** Any



Dimensions in inches and (millimeters)


Absolute Maximum Ratings and Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load, for capacitive load derate current by 20%.

Parameter	Symbols	S1ABD	S1BBB	S1DBD	S1GBD	S1JBD	S1KBD	S1MBD	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_L = 110\text{ }^{\circ}\text{C}$	$I_{F(AV)}$	1							A
Peak Forward Surge Current 8.3 ms Single Half Sine -wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	30							A
Maximum Instantaneous Forward Voltage at 1 A	V_F	1.1							V
Maximum DC Reverse Current $T_a = 25\text{ }^{\circ}\text{C}$ at Rated DC Blocking Voltage $T_a = 100\text{ }^{\circ}\text{C}$	I_R	5 50							μA
Typical Junction Capacitance ¹⁾	C_J	15							pF
Typical Thermal Resistance ²⁾	$R_{\theta JA}$	75							$^{\circ}\text{C/W}$
Operating Junction and Storage Temperature Range	T_j, T_{stg}	- 65 to + 175							$^{\circ}\text{C}$

¹⁾ Measured at 1 MHz and applied reverse voltage of 4 V.

²⁾ P.C.B. mounted with 0.2 X 0.2" (5.0 X 5.0 mm) copper pad areas.



S1ABD THRU S1MBD

