

# SM513G THRU SM516G

## Surface Mount Glass Passivated Rectifiers

Reverse Voltage - 1300 to 1600 V


Forward Current - 1 A

### Features

- Glass passivated device
- Ideal for surface mounted applications
- Low leakage current
- Glass passivated device
- Metallurgically bonded construction

### Mechanical data

- **Case:** MELF (DO-213AB) molded plastic
- **Terminals:** Solder plated, solderable per MIL-STD-750, method 2026
- **Polarity:** Color band denotes cathode end
- **Mounting position:** Any



Plastic case MELF (DO-213AB)  
Dimensions in millimeters

### Maximum Ratings and Electrical characteristics


Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Parameter  | Symbols         | SM513G        | SM516G | Units              |
|--|-----------------|---------------|--------|--------------------|
| Maximum Recurrent Peak Reverse Voltage   | $V_{RRM}$       | 1300          | 1600   | V                  |
| Maximum RMS Voltage  | $V_{RMS}$       | 910           | 1120   | V                  |
| Maximum DC Blocking Voltage  | $V_{DC}$        | 1300          | 1600   | V                  |
| Maximum Average Forward Rectified Current at $T_A = 75^\circ\text{C}$  | $I_{F(AV)}$     | 1             |        | A                  |
| Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)                | $I_{FSM}$       | 40            |        | A                  |
| Maximum Forward Voltage at 1 A   | $V_F$           | 1.1           |        | V                  |
| Maximum Reverse Current<br>at Rated DC Blocking Voltage<br>$T_A = 25^\circ\text{C}$<br>$T_A = 125^\circ\text{C}$ | $I_R$           | 5<br>50       |        | $\mu\text{A}$      |
| Typical Junction Capacitance <sup>1)</sup>   | $C_J$           | 15            |        | pF                 |
| Typical Thermal Resistance <sup>2)</sup>   | $R_{\theta JL}$ | 20            |        | $^\circ\text{C/W}$ |
| Typical Thermal Resistance <sup>3)</sup>   | $R_{\theta JA}$ | 50            |        | $^\circ\text{C/W}$ |
| Operating Temperature Range  | $T_j$           | - 55 to + 175 |        | $^\circ\text{C}$   |
| Storage Temperature Range  | $T_{stg}$       | - 55 to + 175 |        | $^\circ\text{C}$   |

<sup>1)</sup> Measured at 1 MHz and applied reverse voltage of 4 V D.C

<sup>2)</sup> Thermal resistance from junction to lead, 6 mm<sup>2</sup> copper pads to each terminal.

<sup>3)</sup> Thermal resistance from junction to ambient, 6 mm<sup>2</sup> copper pads to each terminal.



# SM513G THRU SM516G

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

